

NMRA	STANDARD
ELEC	CTRICAL
Jul 3, 2024Sep 4, 2024Sep 13, 2024	S-9 Draft

1 General

This STANDARD establishes ELECTRICAL requirements for interchange and safe and satisfactory performance of two rail equipment on model railroads. The requirements in this Standard also address center third rail (or center studs power contact systems with the understanding that the center or third rail (or center studs) provide one of two power conducting rails. Center or third rail (or center studs) equipment must be built or modified to avoid electrical shorts and ensure safe, reliable interchange on two rail layouts. Equipment originally designed and manufactured for center, or third rail (or center studs) operation may not provide insulation between outer gauge rails or the wheels.

2 References

This standard should be interpreted in the context of the following NMRA Standards, Technical Notes, and Technical Information.

2.1 Normative

• NMRA S-5 TRACTION Power Collection.

2.2 Informative

15

20

- NMRA S-9.1 DCC Electrical Standards provides information on maximum and minimum voltages at which
 decoders shall operate and what the command station maximum voltage should be by scale.
- NMRA RP-9 Electrical General provides information on various electrical certifications for safety, operation
 of power supplies and other clarifications.
- NMRA TN-9 Wiring for DC & DCC provides information concerning bus wire resistance, power districts, detection, resistance wheel sets and how these affect performance.

3 Terminology

Term	Definition	
Block Control	A system of insulated sections of track permitting independent control of powered equipment in each insulated section of track. Block Control allows model engineers to run a trains addressing independently powered section(s) of track.	
Command Control	A system permitting powered equipment in the same electrical section of track to be independently controlled. Command Control enables model engineers to run their trains independently.	
Current	A flow of charged particles, such as electrons or ions, moving through an electrical conductor.	
Interchange	A chief objective of NMRA Standards, is the concept of common scale and gauge equipment having ability to operate on other common scale and gauge tracks, modules or layouts created and complying with NMRA standards.	
Outside Third Rail	Outside third rail provides a ground level alternative outside gauge rails to center third rail means of conducting electrical power to powered equipment.	
Overhead Wire or Catenary	Overhead wire provides a high level (above train) alternative to center third rail means of conducting electrical power to powered equipment. Overhead wire systems may be labelled "trolley" systems.	

© 1984 – 2024 National Model Railroad Association, Inc.

S-9 Draft ELECTRICAL

Page 1 of 5 – Jul 3, 2024Sep 4, 2024Sep 13, 2024

^	7	4	
4	_		i
			-

35

40

Term	Definition	
Powered Equipment or Rail Equipment	Motive power, locomotives, engines, and other models capable of self-propulsion on rails. Also referred to a vehicle in other NMRA Standards.	
Three Rail Systems	Three Rail Systems may include: center or third rail, center studs, outside third rail, and overhead wire or catenary. Typically, in three rail systems outer gauge rails are both common electrical returns while the various third rail options listed above carry a positive potential. Third rail system trackage avoids electrical shorts encountered with two rail reverse loops, wyes, and turntables when reversing the physical direction of powered equipment.	
Traction Power Collection	NMRA STANDARD S 5 Traction Power Collection focuses on the relative location or position of scale equipment components for reliable operation with overhead wire or outside third rail applications.	
Two Rail Systems	Two rail track and equipment closely approximate prototype equipment appearance. Electrically two rail systems conduct electrical energy by a positive potential on one rail and a negative potential on the second rail. When/If track turns back upon itself as in reverse loops, wyes, and turntables electrical shorts are encountered requiring more electricity management (insulation, switches, etc.).	
Volt	A unit of electrical potential or electromotive force.	

4 Power

4.1 Full throttle voltage available at the rails or motor shall provide sufficient current for optimal operation in compliance with local safety standards at maximum anticipated load.

4.2 Direct Current motors and other devices in equipment such as lights, smoke units or electrically operated couplers shall be able to withstand without permanent damage maximum peak voltage of as appropriate for each scale and gage in the Table 4.2 below.

Table 4.2 Peak Voltage of Motors, Lights and other Components			
Track Gage	Peak Voltage (DC or DCC)		
>0.6" (16mm)	27v		
<0.6"(16mm) and >0.35" (9mm)	24v		
<0.35(9mm)	12v		

4.3 Alternating Current motors and other devices in the mobile equipment shall be able to operate at 27 VAC max.

4.4

4.54.4 High frequency voltage superimposed upon the rails shall not interfere with the normal operation of Powered Equipment.

When using a power source delivering a wave with greater harmonic content than full wave rectified sine wave, exercise care not to operate in such a manner to exceed the rated current or otherwise overheat the motor.

4.74.6 Power may be supplied to equipment through one or more means to include; rails, center studs, overhead or catenary wires, center or outside third rail, or stored power such as batteries on board powered equipment and/or consisted non-powered equipment, and on-board solar energy conversion.

Formatted: Indent: Left: 0.5", No bullets or numbering

5 Control

45

55

60

- 5.1 Direction control by polarity reversing shall be provided for direct current (DC) motors. Positive potential applied to the positive motor connection either directly or through a <u>Digital Command Control (DCC) decoder</u> battery, or other electrical energy source shall produce forward motion.
- 5.2 For DC equipment, when the "right_hand rail" is positive, the powered equipment shall move forward. The term "right_hand rail" as used herein mean the rail to the right of the observer standing between the rails with their back to the front of the locomotive.
- 5.3 The positive motor terminal shall be connected to the right_hand rail in DC equipment.
- 5.4 For DCC equipment, when positive voltage is applied to the positive motor terminal the locomotive shall move forward.
- 5.5 Typically, AC powered equipment uses a "center or third rail (or stud)" to provide positive potential to motors or decoders and outside rails provide a current return path.
- 5.6 Alternatively, direction control by motor electrical field modification may be provided for alternating current (AC) motors.
- 5.7 Speed control shall be provided by means of voltage adjustment to the motor which may be achieved by devices external or internal to powered equipment.

6 Powered Equipment

- 6.1 Equipment shall be responsive to direction and speed controls of section 5 above.
- 6.2 Metallic couplers shall be insulated from the rails.

7 Non Powered Equipment

- 7.1 Wheelsets shall be insulated to prevent undue conductance between rails.
- 7.2 Where a high resistance path for lighting, detection or other purposes is required, such resistance shall be high enough to prevent significant drop in propulsion power.
- 7.3 Metallic couplers shall be insulated from the rails.

8 Command Control

- 8.1 Standards for Digital Command Control (DCC) are detailed in the S-9.1, S-9.2, and S-9.3 series of NMRA publications.
- 8.2 Command Control systems that do not meet the NMRA DCC Standards may not claim to be DCC 'compatible', but still need to meet the provisions of other sections of this Standard. The DCC certification mark, as used by authorized persons, certifies that the goods are compatible with the NMRA's standards and recommended practices for digital command control.

9 Document History

Date	Description
August 1984	Previous Revision of NMRA STANDARDS S-9 ELECTRICAL

© 1984 – 2024 National Model Railroad Association, Inc.

S-9 Draft ELECTRICAL

Page 3 of 5 – Jul 3, 2024Sep 4, 2024Sep 13, 2024

Commented [Ma1]: See 5.4

70

65

75

Sep 4, 2024 June 27, 2024 Migrated to new template. Included center or third rail as well as Alternating Current (AC), Digital Command Control (DCC), as well as other power sources such as battery on board and solar.



Important Notices and Disclaimers Concerning NMRA Standards Documents

The Standards (S), Recommended Practices (RP), Technical Note (TN), and Translations Technical Information (TI) documents of the National Model Railroad Association ("NMRA Standards documents") are made available for use subject to important notices and legal disclaimers. These notices and disclaimers, or a reference to this page, appear in all standards and may be found under the heading "Important Notices and Disclaimers Concerning NMRA Standards Documents.

Notice and Disclaimer of Liability Concerning the Use of NMRA Standards Documents

NMRA Standards documents are developed within the Standards and Conformance Department of the NMRA in association with certain Working Groups, members, and representatives of manufacturers and sellers. NMRA develops its standards through a consensus development process, which brings together volunteers representing varied viewpoints and interests to achieve the final product. NMRA Standards documents are developed by volunteers with modeling, railroading, engineering, and industry-based expertise. Volunteers are not necessarily members of NMRA, and participate without compensation from NMRA.

NMRA does not warrant or represent the accuracy or completeness of the material contained in NMRA Standards documents, and expressly disclaims all warranties (express, implied and statutory) not included in this or any other document relating to the standard or recommended practice, including, but not limited to, the warranties of: merchantability: fitness for a particular purpose; non-infringement; and quality, accuracy, effectiveness, currency, or completeness of material. In addition, NMRA disclaims any and all conditions relating to results and workmanlike effort. In addition, NMRA does not warrant or represent that the use of the material contained in NMRA Standards documents is free from patent infringement. NMRA Standards documents are supplied "AS IS" and "WITH ALL FAULTS."

Use of NMRA Standards documents is wholly voluntary. The existence of an NMRA Standard or Recommended Practice does not imply that there are no other ways to produce, test, measure, purchase, market, or provide other goods and services related to the scope of the NMRA Standards documents. Furthermore, the viewpoint expressed at the time that NMRA approves or issues a Standard or Recommended Practice is subject to change brought about through developments in the state of the art and comments received from users of NMRA Standards documents

In publishing and making its standards available, NMRA is not suggesting or rendering professional or other services for, or on behalf of, any person or entity, nor is NMRA undertaking to perform any duty owed by any other person or entity to another. Any person utilizing any NMRA Standards document, should rely upon their own independent judgment in the exercise of reasonable care in any given circumstances or, as appropriate, seek the advice of a competent professional in determining the appropriateness of a given NMRA Standards document

IN NO EVENT SHALL NMRA BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO: THE NEED TO PROCURE SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE PUBLICATION, USE OF, OR RELIANCE UPON ANY STANDARD OR RECOMMENDED PRACTICE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE AND REGARDLESS OF WHETHER SLICH DAMAGE WAS FORESEFABLE

NMRA's development of NMRA Standards documents involves the review of documents in English only. In the event that an NMRA Standards document is translated, only the English version published by NMRA is the approved NMRA Standards document.

Official Statements

A statement, written or oral, that is not processed in accordance with NMRA policies for distribution of NMRA communications, or approved by the Board of Directors, an officer or committee chairperson, shall not be considered or inferred to be the official position of NMRA or any of its committees and shall not be considered to be, nor be relied upon as, a formal position of NMRA.

Comments on Standards

Comments for revision of NMRA Standards documents are welcome from any interested party, regardless of membership. However, NMRA does not provide interpretations, consulting information, or advice pertaining to NMRA Standards documents.

Suggestions for changes in documents should be in the form of a proposed change of text, together with appropriate supporting comments. Since NMRA standards represent a consensus of concerned interests, it is important that any responses to comments and questions also receive the concurrence of a balance of interests. For this reason, NMRA, its departments, Working Groups or committees cannot provide an instant response to comments, or questions except in those cases where the matter has previously been addressed. For the same reason, NMRA does not respond to interpretation requests. Any person who would like to participate in evaluating comments or in revisions to NMRA Standards documents may request participation in the relevant NMRA working group.

Laws & Regulations

Users of NMRA Standards documents should consult all applicable laws and regulations. Compliance with the provisions of any NMRA Standards document does not constitute compliance to any applicable regulatory requirements. Implementers of the standard are responsible for observing or referring to the applicable regulatory requirements. NMRA does not, by the publication of NMRA Standards documents, intend to urge action that is not in compliance with applicable laws, and NMRA Standards documents may not be construed as doing so.

Copyrights

NMRA Standards documents are copyrighted by NMRA under US and international copyright laws. They are made available by NMRA and are adopted for a wide variety of both public and private uses. These include both use, by reference, in laws and regulations, and use in private selfregulation, standardization, and the promotion of modeling, structural and engineering practices and methods. By making NMRA Standards documents available for use and adoption by public authorities and private users, NMRA does not waive any rights in copyright to the NMRA Standards documents.

IMPORTANT NOTICE

NMRA Standards documents do not guarantee or ensure safety, security, health, or environmental protection, or ensure against interference with or from other systems, devices or networks. NMRA Standards documents development activities consider research and information presented to the standards development group in developing any safety recommendations. Other information about safety practices, changes in technology or technology implementation, or impact by peripheral systems also may be pertinent to safety considerations during implementation of the standard. Implementers and users of NMRA Standards documents are responsible for determining and complying with all appropriate safety, security, environmental, health, and interference protection practices and all applicable laws and regulations